

NOVA-S



HETRONIC
CENTRAL BALTIC

TECHNICAL SALES SHEET

Transmitter Type: NOVA-S

- **Housing:**
Ergonomically designed housing, belly box style operation
- **Housing Material:**
Impact Resistant Polymer Composite
- **Environmental Protection:**
IP 65
- **Weight:**
369 g (1.3 lbs) includes batteries
- **Dimensions:**
Height: 125 mm, 4.9 in.
Width: 160 mm, 6.3 in.
Depth: 70 mm, 2.8 in.
- **Power Supply:**
3.6 V NiMH rechargeable battery
- **Diagnostics:**
Status LED for operation, low battery indication
- **Operation Time:**
Up to 20 h continuous transmission
- **Typical Transmitter Options**
 - Momentary pushbutton for START/HORN
 - 3-position maintained toggle switch
 - 3-position maintained-off-momentary toggle switch
 - Push mushroom head STOP switch
 - 12 position rotary switch
 - Key switch with removable key cap
- **Frequency Range:**
419 MHz, 429 MHz, 434 MHz, 447 MHz,
458 MHz, 868 MHz
- **RF Unit:**
Type CS synthesized with multiple
frequencies switch selectable
- **Power (RF Output):**
Varies, based on customer requirements
- **Typical Operating Range:**
Up to 100 m (300 ft)
- **Safety Address:**
20-bit (over 999,999 possibilities)
Address Module (ADMO)
- **Safety:**
Active and passive STOP function
Parity and Checksum
- **Temperature Range:**
-25° C to 70° C (-11° F to 158° F)
- **Humidity Range:**
0 - 97% non-condensing
- **Response Time:**
Less than 100 msec.

